

# Tilled to Perfection!

## REVO SERIES ROTARY TILLER

**NIPHA**<sup>®</sup>  
FARM SOLUTIONS



### Revo L series

is specifically crafted for the European and American markets, catering to small-scale farming needs with lower horsepower tractors. It is ideal for gardening and farming purposes.

### Revo M Series

Tillers are robust implements suitable for 25 to 50 HP tractors, specifically designed for challenging conditions, including rocky and demanding soils. Their sturdy construction and heavy-duty Gearbox are engineered to endure rigorous use.

### Revo H Series

are Heavy-duty Rotary Tillers, suitable for 40 to 65 HP tractors. They are specifically designed for challenging conditions, particularly dense and rocky soil. Their robust construction and heavy-duty gearbox are engineered to withstand rigorous use.

### OUR STRENGTHS



Genuine  
Spare Parts



In House Gear Box  
& Blade  
Manufacturing



Award Winner  
Amongst the Largest exporter  
of Agricultural Machinery &  
parts from India.



nipha@niphindia.com

Quality That's World Class



niphafarmsolutions.com

# TECHNICAL SPECIFICATION

Characteristics	Revo L 36	Revo L 42	Revo L 48	Revo L 60	Revo M 53	Revo M 56	Revo M 60	Revo M 72	Revo H 56	Revo H 60	Revo H 72	Revo H 84
Overall Length (mm)	1035	1194	1340	1645	1500	1649	1775	1970	1655	1834	2063	2292
Overall Width (mm)	805	805	805	805	940	940	940	940	1055	1055	1055	1055
Overall Height (mm)	600	600	600	600	720	720	720	720	795	795	795	795
Working Width (mm)	915	1067	1220	1525	1350	1500	1651	1829	1500	1681	1910	2139
Tractor Power (HP)	15-25	20-30	20-35	25-40	25-40	25-40	30-45	35-50	40-55	40-55	45-60	50-65
Three Point Hitch	CAT - I, Compact, Quick Hitch I cat. ASAE				CAT - I, Compact, Quick Hitch I cat. ASAE				CAT - I & II			
No Of Blade (C/L Type)	24	30	36	42	42	42	48	54	36	42	48	54
PTO Speed (RPM)	540				540				540			
Side Transmission Type	Gear				Gear				Gear			
Rotor Shaft Speed RPM @540	245				241				241			
Max Working Depth (mm)	165				180				190			
Rotor Tube Diameter (mm)	70				76				89			
Blade Type (Standard)	Curved				Curved				Curved			
Driveline Safety Device	Slip Clutch				Slip Clutch				Slip Clutch			
Weight (Kg)	153	167	181	200	256	262	285	310	359	390	420	450

## Salient Features

- The dense soil and dirt are loosened to create an outstanding seedbed, ideal for nurturing healthy grass gardens, productive food plots, and well-maintained lawns
- All models are constructed to provide years of reliable performance
- Ideal for any tilling operation

## Optional

- Three point hitch plates for REVO L Series
- REVO L 48 Center mounting available

REVO L - 1.2 (REVO L 48) center mounted model available as per requirement

The company retains full authority to alter the machine's specifications and its components at any time without advance notice

"The weight includes safety guards but does not account for the PTO"

\*The displayed accessories are not included in the standard equipment

## ABOUT NIPHA

NIPHA, established in 1960, is a leading engineering group specializing in farm machinery, railways, power switching, and jute & cotton processing. With a focus on world-class quality, it's recognized as a premier Manufacturing Export House, earning national awards for export excellence since 1975. NIPHA Farm Solutions, a division aimed at providing affordable mechanized farming solutions to small farmers, operates from a new plant in Chandannagar near Kolkata, serving markets worldwide.

### HEAD OFFICE

48 Ganga Jamuna, 28/1 Shakespear Sarani.  
Kolkata -700017, India  
Tel: +91 33 4021 4300 | +91 85850 74007

✉ [nipha@niphindia.com](mailto:nipha@niphindia.com) 🌐 [www.niphafarmsolutions.com](http://www.niphafarmsolutions.com)  
🌐 [niphindia.in](http://niphindia.in) 📍 [niphafarmsolutions](http://niphafarmsolutions)